APPLICATION:		PRODUCT NAME:
		UTILITY SPRAY HOSE ASSEMBLY
JOB NAME:		SPECIAL CONFIGURATION
QUANTITY:	ITEM NO.	MODEL:
		□ 1457
		OPTIONS OR MODIFICATIONS:
		FEATURES
		HOSE * 60" LENGTH
5-3/4" [147mm]		* STAINLESS STEEL END FITTINGS
		* STAINLESS STEEL EXTERNAL JACKET * 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE
		* REPAIRABLE IN-FIELD WITH SIMPLE TOOLS
		UTILITY SPRAY VALVE
		* NOZZLE THREADED INTO VALVE * BRONZE HANDLE - NOT PLASTIC - MEANS FULL "ON"
		* SHOWER SPRAY PATTERN
		* 45° ANGLED HEAD * FITS ALL BRANDS
		* 2.65 GPM AT 80 PSI
		SYSTEM LIMITS
		* TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE: 200 PSI MAX. STATIC
		FRESSURE. 200 FSI MAX. STATIC
	└── 1/4" NPT	SHIPPING WEIGHT * 4.5 LBS
		4.0 200
		FISHER
		FISHER MANUFACTURING COMPANY
(F) ANSI/A112.18.1M		TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com