



#### **FOOTPRINT:**



MODEL	DIM "A"	DIM "B"	DIM "C"
3310	2-3/8"	6"	6"
	[60MM]	[150MM]	[150MM]
3311	2-5/8"	6-1/2"	8"
	[66MM]	[165MM]	[200MM]
3312	3-1/4"	7"	10"
	[83MM]	[177MM]	[250MM]
3313	3-3/4"	7-1/2"	12"
	[98MM]	[188MM]	[300MM]
3314	4-5/8"	8-3/8"	14"
	[115MM]	[212MM]	[350MM]
1627	5-1/8"	9"	16"
	[131MM]	[228MM]	[400MM]

### **ROUGH-IN:**



**(II)** ANSI/A112.18.1M

# FEATURES

☐ OTHER

□ 3313

□ 3314

□ 1627

- \* 8" C/C DECK MOUNT
- \* SWIVELLING SEAT DISKS

□ VANDAL RESISTANT KIT

**OPTIONS OR MODIFICATIONS:** 

- \* HOT SIDE STEM RIGHT HAND
- \* COLD SIDE STEM LEFT HAND
- \* STAINLESS STEEL SEATS
- \* STAINLESS STEEL SEAT SCREWS
- \* STAINLESS STEEL HANDLE SCREWS

WITH 12" SWING SPOUT

WITH 14" SWING SPOUT

WITH 16" SWING SPOUT

□ SUPPLY LINES (24" OR 36") CIRCLE LENGTH
□ DJ SUB-ASSY (7-1/4" OR 13") CIRCLE LENGTH
□ HANDLES (CROSS OR WRIST) CIRCLE STYLE

\* 1/2" SLIP JOINT

### SYSTEM LIMITS

- \* TEMP: 40°F MIN. TO 140°F MAX.
- \* PRESSURE: 200 PSI MAX. STATIC
- \* 2.20 GPM AT 80 PSI

## SHIPPING WEIGHT

\* 5.5 LBS



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com