		,
APPLICATION:		PRODUCT NAME:
		UTILITY SPRAY, DECK MOUNT
JOB NAME:		SPECIAL CONFIGURATION CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.	MODEL:
		□ 2170
7' [177.8		OPTIONS OR MODIFICATIONS:
[177.6	-	SUPPLY LINES (24" OR 36") CIRCLE LENGTH
		☐ ADD-ON FAUCET (6",8",10",12",14",16") CIRCLE LGTH
5-3/4		☐ IN-LINE DUAL CHECK VALVE
[72.9mm]	[146.1mm]	□ VANDAL RESISTANT KIT
		☐ HANDLES (CROSS OR WRIST) CIRCLE STYLE
		□ PIPE HOOK
		□ BRUSH
		OTHER
/	13-1/2" [342.9mm]	FEATURES:
		CONTROL VALVE
		* SINGLE DECK DUAL CONTROL
		* HOT SIDE STEM - RIGHT HAND * COLD SIDE STEM - LEFT HAND
		* SWIVELLING SEAT DISKS
1/2" NPT ———————————————————————————————————		* STAINLESS STEEL SEATS
		* STAINNESS STEEL SEAT SCREWS * STAINLESS STEEL HANDLE SCREWS
1/2" NPT FEMALE		* FLEXIBLE INLET HOSES
		HOSE
		* 60" LENGTH
		* STAINLESS STEEL END FITTINGS * STAINLESS STEEL EXTERNAL JACKET
		* 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE
		* REPAIRABLE IN FIELD WITH SIMPLE TOOLS
		UTILITY SPRAY VALVE
		* NOZZLE THREADED INTO VALVE * 2.65 GPM AT 80 PSI
		* 45° ANGLED HEAD
		* SHOWER SPRAY PATTERN
		SWIVEL ELBOW
		* 360° TURNING RADIUS
		SYSTEM LIMITS
		* TEMP: 40°F MIN. TO 140°F MAX. * PRESSURE 200 PSI MAX. STATIC
ROUGH-IN:		SUIDDING WEIGHT
		SHIPPING WEIGHT * 9.0 LBS
Q	01-1/4 "	
√ [31.8mm]		
	\	

ANSI/A112.18.1M



SPEC. 2170 REV.D