APPLICATION:		PRODUCT NAME:
		PRE-RINSE, SWIVEL STYLE, DECK MOUNT
JOB NAME:		SPECIAL CONFIGURATION  CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.	MODEL:  ☐ 2311 ULTRA SPRAY VALVE NO WALL BRACKET  ☐ 2311-WB ULTRA SPRAY VALVE W/ WALL BRACKET
<b>©</b>		OPTIONS OR MODIFICATIONS:  SUPPLY LINES (24" OR 36") CIRCLE LENGTH  ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE  IN-LINE DUAL CHECK VALVE  PIPE HOOK  BRUSH  HANDLES (CROSS OR WRIST) CIRCLE STYLE  VANDAL RESISTANT KIT
	37" [940mm]	CONTROL VALVE  * 8" DECK MOUNT  * INTERNAL SPRING LOADED CHECK VALVES  * HOT SIDE STEM - RIGHT HAND  * COLD SIDE STEM - LEFT HAND  * SWIVELLING SEAT DISKS  * STAINLESS STEEL SEATS  * STAINLESS STEEL SEAT SCREWS  * STAINLESS STEEL HANDLE SCREWS
	2" ————————————————————————————————————	HOSE  * 15-1/2" LENGTH  * STAINLESS STEEL END FITTINGS

[203mm]

1/2" SLIP JOINT

- \* STAINLESS STEEL END FITTINGS
- \* STAINLESS STEEL EXTERNAL JACKET
- \* 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE

**ULTRA SPRAY VALVE** 

- \* LOWEST ENERGY USER 1.15 GPM @ 60 PSI
- \* CLEANS FASTER TEST PROVEN
- \* ENGINEERED TO LAST NO 'O' RINGS TO LEAK
- \* INTERCHANGEABLE FITS ALL BRANDS

SYSTEM LIMITS


- \* TEMP: 40°F MIN. TO 140°F MAX.
- \* PRESSURE: 200 PSI MAX. STATIC

SHIPPING WEIGHT

\* 12.0 LBS



[203mm]



EPAct 2005 Compliant



ANSI/A112.18.1M



TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com