
APPLICATION:		PRODUCT NAME:
		PRE-RINSE, SWIVEL STYLE, DECK MOUNT
JOB NAME:		SPECIAL CONFIGURATION  CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.   1-1/2" ─────	MODEL:  2511 ULTRA SPRAY VALVE NO WALL BRACKET  2511-WB ULTRA SPRAY VALVE W/ WALL BRACKET
[292mm]		OPTIONS OR MODIFICATIONS:  SUPPLY LINES (24" OR 36") CIRCLE LENGTH  ADD-ON FAUCET (6", 8", 10", 12", 14", 16") CIRCLE  IN-LINE DUAL CHECK VALVE  PIPE HOOK  BRUSH  HANDLES (CROSS OR WRIST) CIRCLE STYLE  VANDAL RESISTANT KIT
	37" [940mm]	FEATURES  CONTROL VALVE  * 4" DECK MOUNT  * INTERNAL SPRING LOADED CHECK VALVES  * HOT SIDE STEM - RIGHT HAND  * COLD SIDE STEM - LEFT HAND  * SWIVELLING SEAT DISKS  * STAINLESS STEEL SEATS  * STAINLESS STEEL SEAT SCREWS  * STAINLESS STEEL HANDLE SCREWS
<b></b> 8"	8"	HOSE  * 15-1/2" LENGTH  * STAINLESS STEEL END FITTINGS  * STAINLESS STEEL EXTERNAL JACKET  * 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE
	[203m	nm] ULTRA SPRAY VALVE  * LOWEST ENERGY USER - 1.15 GPM @ 60 PSI

**ROUGH-IN:** 

4" [102mm]



1/2" SLIP JOINT

ANSI/A112.18.1M

(1)

FISHER MANUFACTURING COMPANY TOLL FREE: 800-421-6162 - FAX: 800-832-8238 information@fisher-mfg.com - www.fisher-mfg.com

\* CLEANS FASTER - TEST PROVEN

\* TEMP: 40°F MIN. TO 140°F MAX.

\* PRESSURE: 200 PSI MAX. STATIC

SYSTEM LIMITS

SHIPPING WEIGHT \* 12.0 LBS

\* ENGINEERED TO LAST - NO 'O' RINGS TO LEAK \* INTERCHANGEABLE - FITS ALL BRANDS