APPLICATION:		PRODUCT NAME:
		SPRAY VALVE WITH 36" HOSE
JOB NAME:		SPECIAL CONFIGURATION  CHECK BASE MODEL AND OPTIONS
QUANTITY:	ITEM NO.	MODEL:
		■ 2911 WITH ULTRA SRAY VALVE
		OPTIONS OR MODIFICATIONS:  □ OTHER
		FEATURES
1/4" NPT N	IALE HOSE	HOSE  * 36" LENGTH  * STAINLESS STEEL END FITTINGS  * STAINLESS STEEL EXTERNAL JACKET  * 3-PLY FIBER REINFORCED INTERNAL RUBBER HOSE  * REPAIRABLE IN-FIELD WITH SIMPLE TOOLS  ULTRA SPRAY VALVE  * LOWEST ENERGY USER - 1.15 GPM @ 60 PSI  * CLEANS FASTER - TEST PROVEN  * ENGINEERED TO LAST - NO 'O' RINGS TO LEAK  * INTERCHANGEABLE - FITS ALL BRANDS  SYSTEM LIMITS  * TEMP: 40°F MIN. TO 140°F MAX.  * PRESSURE: 200 PSI MAX. STATIC
		FISHER

EPAct 2005 Compliant